

WAXMAN STAINLESS PUTTY

**FOR CHEMICAL EMERGENCY:** Spill, Leak, Fire, Exposure, or Accident – Call INFOTRAC – Day or Night: 1-800-535-5053  
**THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name: CLEANING COMPOUNDS, NOI CAS NO.: MIXTURE  
Chemical Family: OIL UN/NA#: N/R  
DOT Hazard Class: N/R DATE OF ISSUE: 1/01

SECTION 1 – HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS#	TLV/PEL	AGENCY	TYPE	SARA-313(%Range)
NONE					

SECTION II – EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** Flush the contaminated eye(s) with water for 15 minutes. If irritation persists, obtain medical advise.  
**SKIN CONTACT:** Remove contaminated shoes and clothing and cleanse affected areas thoroughly by washing with mild soap and water. If irritation persists seek medical attention.  
**INHALATION:** (breathing) Not expected to be a hazard under normal operating conditions.  
**INGESTION:** (swallowing) Rinse mouth with water. Do not induce vomiting. Seek medical advice immediately.

SECTION III – HEALTH HAZARDS/ROUTES OF ENTRY

**EYE CONTACT:** One or more components of this material may be an eye irritant.  
**SKIN CONTACT:** Continuous contact with this material may cause drying of skin. Chemical itself is an irritant or sensitizer.  
**INHALATION:** (breathing) Not expected to be a hazard under normal operating conditions..  
**INGESTION:** (swallowing) Ingestion of large quantities may cause the following: Irritation of digestive tract, intestinal obstruction or constipation.

SECTION IV – SPECIAL PROTECTION INFORMATION

**VENTILATION:** If current ventilation practices are not adequate to maintain airborne concentrations below established exposure limits (see Section I), additional ventilation or exhaust systems may be required.  
**RESPIRATORY PROTECTION:** Not necessary under normal use.  
**PROTECTIVE GLOVES:** The use of gloves impermeable to the specific material handled is advised to prevent possible irritation.  
**EYE PROTECTION:** Approved eye protection to safeguard against potential eye contact is strongly recommended.

SECTION V – REACTIVITY DATA

**STABILITY:** Stable  
**INCOMPATIBILITY:** (material to avoid) This product is incompatible with: *Oxidizing agents, strong acids and bases.*  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide.  
**HAZARDOUS POLYMERIZATION:** Will not occur.

SECTION VI – SPILL OR LEAK PROCEDURES

**PRECAUTIONS IN CASE OF LEAK OR SPILL:** If spill occurs, material should be cleaned-up with an appropriate absorbent.  
**WASTE DISPOSAL METHOD:** Dispose of product in accordance with local, county, state, and federal regulations.

SECTION VII – STORAGE AND SPECIAL PRECAUTIONS

**HANDLING AND STORAGE PRECAUTIONS:** Do not get in eyes, skin or clothing. Keep containers tightly closed, cool and dry. Use and store this product with adequate ventilation. Use good personal hygiene practices. Containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION VIII – FIRE AND EXPLOSION HAZARD DATA

**EXTINGUISHING MEDIA:** Extinguish with dry chemical, CO<sub>2</sub>, or a universal type foam.  
**FIRE AND EXPLOSION HAZARD:** May decompose during contact with flames, heating elements, or in combustion engines releasing irritating gases. Container may explode if heated due to resulting pressure rise.

## WAXMAN STAINLESS PUTTY

**FIRE FIGHTING PROCEDURES:** Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section IV). Water spray may be useful in minimizing or dispersing vapors and cooling equipment exposed to heat and flame.

<b>SECTION IX – PHYSICAL DATA</b>
-----------------------------------

<b>APPROXIMATE BOILING POINT (DEGF): &gt;400</b>	<b>PER CENT VOLATILE: NONE</b>
<b>SPECIFIC GRAVITY (68F): &gt;1</b>	<b>FLASH POINT (TCC, DEG F): &gt;400</b>
<b>RELATIVE EVAPORATION RATE (ESTIMATED): &lt;1</b>	<b>PERCENT SOLUBILITY IN WATER: NEGLIBIBLE</b>
<b>VAPOR PRESSURE @20C mmHg (CALCULATED): &lt;1</b>	

<b>SECTION X – OTHER REGULATORY DATA</b>
--

<b><u>SARA</u></b>	<b><u>HMIS</u></b>
<b>SECTION 302: NONE</b>	<b>Health: 0</b>
<b>SECTION 311 &amp; 312: NONE</b>	<b>Flammability: 0</b>
<b>SECTION 313: See Section II</b>	<b>Reactivity: 0</b>

**TSCA**  
All components are in full compliance  
With the TSCA Inventory.

**CALIFORNIA PROPOSITION 65**  
NOT LISTED

**RCRA**  
NOT REGULATED

**CERCLA**  
NOT REGULATED

**CARCINOGENICITY:**  
NOT LISTED with NTP or IARC

**NOTICE**

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufactures and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.